



## Certificate No: MCS BBA 0156

### Technology:

### MCS 012 – Pitched Roof Installation Kits

### Products:

### GSE Integration Mounting Systems

Components	GSE Integration Frames: Mounting Plate Nylon Block Side flashing EPDM seal Clamps
Installation Type	Roof integrated
Permissible roof pitch (Angle °)	1.5° – 50°
Roofing substrate minimum requirements	Slated or tiled roofs
Maximum design wind uplift resistance (kPa) <i>Calculated by dividing the characteristic wind uplift resistance by the partial safety factor shown below.</i>	1.5
Partial (safety) factor(s)	1.1
Fire classification to EN 13501-5 : 2005 + A1 : 2009	Sunmodule Plus SW 250 Poly – B <sub>ROOF</sub> (t4) Trina Solar TSM DC05A.08 – B <sub>ROOF</sub> (t4) Trina Solar TSM-DC05A.05 – B <sub>ROOF</sub> (t4) Perlight PLM 250MB-60-Delta – B <sub>ROOF</sub> (t4) Perlight Intenergy INE-250-P-60 – B <sub>ROOF</sub> (t4) Perlight Intenergy INE-285MB-60 – B <sub>ROOF</sub> (t4) Sunpower SPR E20-327 – B <sub>ROOF</sub> (t4) Canadian Solar CS6P-265P – B <sub>ROOF</sub> (t4) Canadian Solar CS6P-265M – B <sub>ROOF</sub> (t4) JA Solar 60/275-295 – B <sub>ROOF</sub> (t4) JA Solar JAP 6 (SE) – B <sub>ROOF</sub> (t4) JA Solar JAM 6 (K) (BK)-60-285/4BB – B <sub>ROOF</sub> (t4) Sapphire Solar SS250P/60 – B <sub>ROOF</sub> (t4) Eging EG-285-M60-C – B <sub>ROOF</sub> (t4) Solar World SW-275 MB-60 – B <sub>ROOF</sub> (t4) Phono Solar PS 250 – B <sub>ROOF</sub> (t4) Seraphin SRP 250-6PB – B <sub>ROOF</sub> (t4) Seraphin SRP 250-6MB – B <sub>ROOF</sub> (t4) LG LG260/250/245-S1C – B <sub>ROOF</sub> (t4)



<p>Fire classification to EN 13501-5 : 2005 + A1 : 2009</p>	<p>BenQ Solar BenQ AUO PM060MW2 – B<sub>ROOF</sub>(t4) BenQ Solar BenQ AUO PM096B00 – B<sub>ROOF</sub>(t4) LG LG NeON 2 Black – B<sub>ROOF</sub>(t4) LG LG NeON 2 – B<sub>ROOF</sub>(t4) Panasonic VBHN245SJ25 – B<sub>ROOF</sub>(t4) Shinetime XTM6-60-250BK – B<sub>ROOF</sub>(t4) Risen Risen RSM-60-6-250P – B<sub>ROOF</sub>(t4) REC Peak Energy 250PE – B<sub>ROOF</sub>(t4) Axitec AC-270M/156-60S R35 – B<sub>ROOF</sub>(t4)</p> <p>Products tested for fire classification are as stated above.</p> <p>The fire performance rating applies to the roofing kit when used with the family of modules from which the tested modules came, or other modules that have identical material specification and design of: frame, coversheet, encapsulant, backing sheet and sealant.</p>
---	---

GSE Integration  
155-159 rue du docteur Bauer  
93400 Saint-Ouen  
France

The BBA (British Board of Agrément) has issued this Microgeneration Certification Scheme (MCS) Certificate to the company and products named above, in recognition of the products's compliance with the MCS Scheme Requirements for the technology named above.

On behalf of the British Board of Agrément

Date of Fourth issue: 22 May 2017

*Certificate amended on 30 May 2018 to include change of company name.*

Claire Curtis-Thomas

Chief Executive

*The BBA is a UKAS accredited certification body — Number 113. The schedule of the current scope of accreditation for product certification is available in pdf format via the UKAS link on the BBA website at [www.bbacerts.co.uk](http://www.bbacerts.co.uk)*

*Readers are advised to check the validity and latest issue number of this MCS Certificate by either referring to the BBA website or contacting the BBA direct.*

British Board of Agrément  
Bucknalls Lane  
Watford  
Herts WD25 9BA

©2017

tel: 01923 665300  
fax: 01923 665301  
[clientservices@bbacerts.co.uk](mailto:clientservices@bbacerts.co.uk)  
[www.bbacerts.co.uk](http://www.bbacerts.co.uk)